

Cement Based Multi-Coat Acrylic Decking



K
O
V
E
R

K
R
E
T
E
™

S
Y
S
T
E
M
S

PRODUCT INFORMATION

USE

- Driveways
- Patios
- Pool Decks
- Porches

ADVANTAGES

- Unmatched warranty
- Excellent adhesion and weathering
- Retards salt/water penetration
- Slip resistant surface can be achieved
- Quick installation
- Cooler than regular concrete
- Can be applied on fresh concrete
- Freeze-thaw resistant

DESCRIPTION

The **KOVER KRETE™ SYSTEM** is a combination of an acrylic polymer, special type white cements and aggregates, that combine to form a white colored, durable, resilient surface finish that has exceptional wear resistance.

The **KOVER KRETE™ SYSTEM** can be integrally colored with colors displayed on the **KOVER KRETE™ INTEGRATED COLOR CHART**, or color sealed with **KOVER GARD™**.

KOVER GARD™ is a high performance floor coating primarily designed to color, protect, and preserve new and old concrete walking surfaces. It is formulated with specially selected resins, pigments, and fillers that provide a durable, colored surface highly resistant to abrasion.

The **KOVER KRETE™ SYSTEM** is available as a one-part, Just-Add-Water mix, as well as our traditional two-part system including dry mix and **LIQUID ACTIVATOR™**.

The **LIQUID ACTIVATOR™** used in mixing the two-part **KOVER KRETE™ SYSTEM** is an acrylic polymer emulsion, that adds adhesive properties,

water repellence, and more flexural strength.

The **KOVER KRETE™ SYSTEM** is a multi-coat system. It can be applied over existing concrete at a 1/4" (6 mm) thickness, which permits many existing elevations to remain basically unchanged. The important characteristics of the **KOVER KRETE™ SYSTEM** are its extra-ordinary adhesion coupled with its ability to withstand prolonged pedestrian and vehicular traffic. In these respects, the material is far superior to conventional cementitious products.

The spray application textures, patterns, and colors, enable the creation of many unique designs at a fraction of the time and expense required by other traditional type material.

Creating a solid surface, the **KOVER KRETE™ SYSTEM** eliminates weed growth and dirt collection, which is prevalent in many paved system joint areas.

DESIGN AND COLOR OPTIONS

The **KOVER KRETE™ SYSTEM** is a white and gray colored product. It can be colored in a variety of other colors with the addition of **DRY CEMENT COLOR PACKS**. SEE **KOVER KRETE™ COLOR CHART**.

PRODUCT COVERAGE

KOVER KRETE™ DRY or KOVER KRETE™ INSTANT
200 sq. ft. at 1/8" thickness (Texture Only)

KOVER GARD™ WB (1 GAL)
100 Sq. Ft. (Two Coats)

KLEAR GARD™ WB (KLEAR SEAL) (1 GAL)
200 Sq. Ft. Of **KOVER GARD** sealed texture (one coat)

KLEAR GARD™ SB (1 GAL)
100 Sq. Ft. Of Integral Color **KOVER KRETE**

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com

**TECHNICAL DATA
KOVER KRETE™ SYSTEM**

| | |
|------------------------------------|------------------|
| Tensile Strength* | 615 PSI |
| Compressive Strength* | 7814 PSI |
| Flexural Strength* | 1585 PSI |
| Shear Bond* | - 650 (C) |
| Impact Strength* | 16 |
| Abrasion | 1.15** |

*28 day air cure and ** Lower values indicate better abrasion resistance.

PACKAGING

| | |
|------------------------------|--------------------------|
| Dry Cement Mix | 50 lb Bag |
| Dry Cement Color Packs | 1-3 lb. Bags |
| Instant Krete | 50 lb. Bag |
| Kover Gard | 1 gal. Can / 5 gal Pail |
| Activator | 5 gal. Pail |
| Relaxer | 1 qt. Bottle / 1gal. Can |
| Klear Gard WB | 1, 5 gal. Pail |
| Klear Gard SB | 1, 5 gal. Pail |

defects determined by accepted test methods by an independent party. Contract Packaging Inc. liability in connection to the sale of its products, is limited to the purchase price of its products only. No other warranty is expressed or implied. Applicator is required to use the complete KOVER KRETE™ SYSTEM, KOVER KRETE™ DRY MIX or KOVER KRETE™ INSTANT, plus ACTIVATOR™ or KEYBOND™, plus KOVER GARD™ WB or SB SEALER, or KLEAR GARD WB or SB™ SEALER for WARRANTY. ANY SUBSTITUTIONS WILL VOID WARRANTY.

LIMITED WARRANTY NOTICE

KOVER KRETE™ is installed for use as a decorative surface covering for residential and commercial vehicle drive areas, as well as any pedestrian walkway/decking. KOVER KRETE™ must be applied in accordance with printed installation procedures. ANY DELAMINATION DIRECTLY RELATED AND ATTRIBUTED TO THE UNDERLYING CONCRETE SUBSTRATE IS NOT COVERED BY THE WARRANTY. Examples: cracking, settling, expansion and contraction movement, deteriorations, and moisture penetration through concrete or cracks. The concrete substrate to which KOVER KRETE™ is being applied must be properly cleaned and prepped prior to application according to Kover Krete™ System standards, surface must be sound, grease free and uncontaminated by any substance that could prevent bonding. In the event delamination occurs, the original applicator must notify Contract Packaging Inc. in writing that delamination occurred strictly from bond failure of the KOVER KRETE™ material and not from the underlying concrete substrate. CONTRACT PACKAGING INC. agrees to replace any materials purchased free of charge, for the specific area where the delamination occurred and when material defect is the proven cause of any

Manufactured by
CONTRACT PACKAGING INC.
22 N. Dollins Avenue - Orlando, FL 32805
Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com