

Brilliant Finish™

Seal Finish

Mirror Finish™

Wet Look Gloss Ultra High-Speed Floor Finish



PRODUCT AND APPLICATION GUIDE

PACKAGING

BRILLIANT FINISH™

1, 5 gal. pails / 55 gal. drums

MIRROR FINISH™

1, 5 gal. pails and 55 gal. drums

COVERAGE PER GALLON

(5 gallons = 1,000 sq. ft. @ 4 coats)

1st coat 800-1000 sq. ft.

Multiple coats 1200 sq. ft.

MIRROR FINISH™ is the ultimate in a high solids floor finish. This versatile easy to apply product holds up to heavy traffic, detergent scrubbing and ultra-high speed burnishing. Ideal for low maintenance programs. Note:

Mirror Finish™ is classified by Underwriter's Laboratories, Inc. as to slip resistance only. 59X9

BRILLIANT FINISH™ is a seal and finish all-in-one product that displays exceptional durability and gloss. Use on brick, slate, terrazzo, quarry tile, unglazed ceramic, Mexican tile, concrete and resilient floors. The durability of BRILLIANT FINISH™ extends wear in high traffic areas and reduces marking and scuffing and is easily repaired with burnishing or a re-coat. This product dries to a clear brilliant gloss with excellent leveling and bonding that eliminates problems.

SURFACE PREPARATION

To put down MIRROR FINISH™ or BRILLIANT FINISH™ the floor needs to be clean and free of dirt. It should be cleaned with a neutral cleaner. If any old sealers or finishes are on the floor they need to be removed using CITRA-KLEAN™ and a wet-dry vac. The floor should be neutralized and then thoroughly rinsed. Remove residue using a wet-dry vac.

PRODUCT APPLICATION

After the floor is dry apply 2 to 4 coats (minimum of 4

coats on commercial applications) of MIRROR FINISH™ or BRILLIANT FINISH™ allowing 30 to 60 minutes dry time between coats. Use a rayon finish mop (must use a finish mop) to apply the seal. A finish mop release and spreads the seal evenly. Rinse the finish mop with clear water to remove any loose lint prior to using it.

If a higher gloss is needed, apply a coat of MIRROR FINISH™ over the BRILLIANT FINISH™. Both of these finishes can be burnished using a (1500-3000 RPM burnisher).

MAINTENANCE

Dust mop daily with treated dust mop. Damp mop or auto mop daily with a neutral floor cleaner. Burnish with a 1500-3000 rpm burnisher.

FUTURE CARE

When burnishing no longer restores gloss, scrub floor with CITRA-KLEAN™ and apply 2 coats of BRILLIANT FINISH™ or MIRROR FINISH™.

CAUTION

Keep out of reach of children! Any liquids spilled on a finished floor will cause a hazardous, slippery condition. Clean up of spills should have immediate attention. **Do not mix with other chemicals! It is recommended that protective eye wear and gloves be worn when using these products.**

FIRST AID

Avoid eye contact. For eye contact, rinse with water. If irritation persists, get medical help. **Do not swallow.** If swallowed get medical help immediately.

WARNING

Do not pour unused finish back into container as it will damage the product.

STORAGE AND CONTAINER DISPOSAL

When not in use, store in original closed container in a cool area out of direct sunlight. Triple rinse or equivalent. Puncture and dispose of by procedures approved of by state and local authorities.

HAZARDOUS INGREDIENTS

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com

MIRROR FINISH™

CAS # 111-90-0: Diethyleneglycolmonoethylether
CAS # 34590-94-8: Dipropyleneglycolmonomethylether
CAS # 25265-77-4: 2,2,4-Trimethyl-1,
3-pentanediolmonoisobutyrate
CAS# 78-51-3: Tributoxyethylphosphate

Hazard Rating: Fire-0 (Insignificant),
Health-1 (Slight), Reactivity-0 (Insignificant)

BRILLIANT FINISH™

CAS #34590-94-8: Dipropyleneglycolmonomethylether
CAS #25265-77-4: 2,2,4-trimethyl-1,
3-pentanediol monoisobutyrate
CAS #6846-50-0: 2,2,4-trimethyl-1,
3-pentanediol diisobutyrate
CAS #78-51-3: Tributoxyethylphosphate

Hazard Rating: Fire-0 (Insignificant),
Health-1 (Slight), Reactivity-0 (Insignificant)

24-HOUR EMERGENCY NUMBER

1-800-535-5053

LIMITED WARRANTY NOTICE

Contract Packaging Inc. products are designed to be used in the construction industry and should be applied by competent persons in accordance with current published instructions. We cannot be held responsible for difficulty caused by other materials and conditions, or by

inferior workmanship. Seller reserves the right to have the true cause of any difficulty determined by accepted test methods by an independent party. Any claim regarding product defect must be received in writing (1) year from day of shipment. No claim will be considered without such written notice or after the specified time interval.

DISCLAIMER OF WARRANTIES AND LIMITATIONS OF LIABILITY

Contract Packaging Inc. (Seller) warrants that if any goods supplied prove defective in workmanship or material that Seller shall replace them or refund their purchase price. This warranty is made in lieu of any and all other warranties, expressed or implied. Including the warranties of merchantability and/or fitness, which are hereby disclaimed. It is understood and agreed that buyer's sole remedy, and therefore Seller's liability, whether in contract, tort, under any warranty, in negligence, or otherwise shall be limited to the return of the purchase price paid by purchaser or replacement of any defective goods sold by Seller and under no circumstances shall Seller be liable for special, indirect or consequential damages. The price stated for the goods is a consideration in limiting Seller's liability. Any liability or risk resulting from the use of this product is assumed by the purchaser/user except where a specific warranty is provided by the manufacturer in writing. Before application, the purchaser/user shall determine the suitability of the product for his intended use and purchaser/user assumes all liabilities and risk, whatsoever in connection therewith. The terms of this warranty notice may not be orally modified. Any substitutions will void warranty.

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com