

# Liquid Antique™



K  
O  
V  
E  
R  
  
K  
R  
E  
T  
E  
™  
  
S  
Y  
S  
T  
E  
M  
S

## PRODUCT / APPLICATION GUIDE

### PACKAGING

LIQUID ANTIQUE™ ...1, 5 gal. pails

### DESCRIPTION

LIQUID ANTIQUE™ is a solvent-based formula with acrylic copolymer resins and light-fast, permanent, and alkali proof pigments to produce an antique finish on concrete surfaces, and stamped overlayment systems.

### ADVANTAGES

- Adds decorative accent colors when applied to concrete surfaces and stamped overlayment systems.
- Resistant to salt spray, acids, alkali, water, and ultraviolet rays
- High resistance to traffic

### COVERAGE

500 square feet per 5 gal. pail

### TECHNICAL DATA

- Form: slightly viscous, opaque liquid.
- Specific Gravity: 1.08
- Pigment/Vehicle: 0.93/1.00
- Volume Solids: 10% to 12.5%
- Weight Solids 37% +/-5%
- Gloss 60° on glass: 75
- Weatherometer G23F Type: 2000 hours plus
- Hurricane force water TT-C-555B on effect
- Moisture vapor permeability ASTM E96-66:0.0001
- Abrasion Resistance: 12.5 gram loss (Tabor)
- Hardness (Toukon): 12-1000 cycles
- Flash Point:>100° F CC
- Glass Transition Temperature: 50Tg °C

### SAFETY PRECAUTIONS

Avoid prolonged contact with skin. If material contacts skin, wash thoroughly with soap and water

- Take precautions to keep from splashing in eyes
- Avoid prolonged breathing of vapors
- Ventilate area being coated during application and drying periods
- Do not smoke during application or drying periods
- Do not apply where open flame or sparks exist
- Use commercial "water-less" hand cleaners.

### APPLICATION

Application with pump-up bug sprayer. A one-coat application is recommended by Kover Krete™ Systems. Stamped Overlayment or concrete needs to dry overnight before applying Liquid Antique™. Liquid Antique™ should reach a "Tacky Dry" state before applying two coats of Klear Seal SB™ using a 1 1/4"-1 1/2" lambs wool roller nap. This generally means waiting 20 to 30 minutes between coats. However, job site conditions and weather may cause this time to vary. If bubbling should occur roll back over surface before surface dries to insure bubble-free surface or lightly mist xylene on deck with bug sprayer.

### MAINTENANCE

Kover Krete™ Systems recommends that the surface be kept clean and soil free. The surface should be cleaned with soap/detergent and water on a regular basis. In the future, an additional coat of seal may be required depending upon exposure and traffic. Rinse thoroughly and completely with water after cleaning.

### CLEAN UP

Clean up with typical and accessible solvent based materials such as Xylene or Tolulene.

### LIMITED WARRANTY NOTICE

Contract Packaging Inc. products are designed to be used in the construction industry and should be applied by competent persons in accordance with current published instructions. We cannot be held responsible for difficulty caused by other materials and conditions, or by inferior workmanship. Seller reserves the right to have the true cause of any difficulty determined by accepted test methods by an independent party. Any claim regarding product defect must be received in writing (1) year from day of shipment. No claim will be considered without such written notice or after the specified time interval.

### DISCLAIMER OF WARRANTIES AND

Manufactured by  
**CONTRACT PACKAGING INC.**  
22 N. Dollins Avenue - Orlando, FL 32805  
Tel. (407) 246-7797 - Fax. (407) 481-2261 - [www.koverkrete.com](http://www.koverkrete.com)

## **LIMITATIONS OF LIABILITY**

Contract Packaging Inc. (Seller) warrants that if any goods supplied prove defective in workmanship or material that Seller shall replace them or refund their purchase price. This warranty is made in lieu of any and all other warranties, expressed or implied. Including the warranties of merchantability and/or fitness, which are hereby disclaimed. It is understood and agreed that buyer's sole remedy, and therefore Seller's liability, whether in contract, tort, under any warranty, in negligence, or otherwise shall be limited to the return of the purchase price paid by purchaser or replacement of any defective goods sold by Seller and under no circumstances shall Seller be liable for special, indirect or consequential damages. The price stated for the goods is a consideration in limiting Seller's liability. Any liability or risk resulting from the use of this product is assumed by the purchaser/user except where a specific warranty is provided by the manufacturer in writing. Before application, the purchaser/user shall determine the suitability of the product for his intended use and purchaser/user assumes all liabilities and risk, whatsoever in connection therewith. The terms of this warranty notice may not be orally modified. Any substitutions will void warranty.