

Kover Krete™ Stamp Mix



K
O
V
E
R
K
R
E
T
E
S
Y
S
T
E
M

Material Safety Data Sheet

PRODUCT: Kover Krete™ Stamp Mix (Page 1 of 2)

1. IDENTIFICATION OF SUBSTANCE

- **Product details**
- **Trade name:** Kover Krete™ Stamp Mix
- **Manufacturer/Supplier:** Contract Packaging, Inc., 22 N. Dollins Ave, Orlando, FL 32805
Tel. (407) 246-7797, Fax. (407) 481-2261, www.koverkrete.com

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2. HAZARDOUS INGREDIENTS

- | Hazardous components: | OSHA PEL | ACGIH TLV | Other Limits | Contents% |
|---|-----------------------------|---------------------------|---------------------|------------------|
| CAS# 65997-15-1 Portland Cement | 8H TWA 10 mg/m ³ | 30 mppcf | Total dust | < 50% |
| CAS# 14808-60-7 Silica, Crystalline
Quartz | 0.1mg Quartz m ³ | TWA 0.1 mg/m ³ | Respirable dust | ~60% |

- **General Information:** To the best of our knowledge the information contained herein is correct. Contract Packaging, Inc. assumes no responsibility for accuracy or completeness. User is responsible for suitability.

FOR INDUSTRIAL USE ONLY

- **HMIS RATING:** Health-1 Flammability-0 Reactivity-1 Protection-E

3. PHYSICAL/CHEMICAL CHARACTERISTICS

- | | | | |
|---------------------------------|-----------------------|--|---------|
| Boiling Point: | N/A | Specific Gravity (H₂O=1) | 2.2-3.0 |
| Vapor Pressure (mm Hg) | N/A | Melting Point | N/A |
| Vapor Density (Air=1) | N/A | Evaporation Rate (Butyl Acetate=1) | N/A |
| Solubility in Water: | Slight | Viscosity of Liquid | N/A |
| Appearance, Odor, Color: | White Powder, No Odor | | |

4. FIRE AND EXPLOSION HAZARD DATA

- **Flash Point (Method Used):** N/A
- **Flammable Limits:** Non-Flammable **LEL:** N/A **UEL:** N/A
- **Extinguishing Media:** Water of Multi-Purpose Dry Chemical
- **Special Fire Fighting Procedures:** Water may cause material to set up. A slurry of material can plug drains. Wet cement can dry the skin and cause alkali burns.
- **Unusual Fire and Explosion Hazards:** No fire or explosive hazards.

5. REACTIVITY DATA

- **Stability:** Stable (Although no hazardous reaction will occur, material should be kept dry.)
- **Conditions to Avoid:** N/A
- **Incompatibility (Materials to Avoid):** Acid
- **Hazardous Decomposition or Byproducts:** N/A
- **Hazardous Polymerization:** Will not occur
- **Conditions to Avoid:** Not applicable

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com

6. HEALTH HAZARD DATA

- **Health Hazard**
- **Route(s) of Entry:**
 - Eyes-** Dust Irritant
 - Inhalation-** Overexposure
 - Skin-** Abrasive
 - Ingestion-** May Cause Obstruction
- **Health Hazards (Acute and Chronic):** Inhalation of Silica Dust can produce Silicosis, which is a chronic, slowly developing disease. Avoid over exposure to the airborne dust. ACUTE: Wet cement can dry the skin and cause Alkali burns. Cement dust can irritate the eyes and upper respiratory system. CHRONIC: Cement dust can cause inflammation of the lining tissue of the interior of the nose and inflammation of the cornea. Hypersensitive individuals may develop an allergic dermatitis.
- **Carcinogen: Classified Group 2A by IARC**
 - NTP:** N/A **IARC Monographs:** Limited Evidence as Human Carcinogen
 - OSHA Regulated:** See ingredients under Section 2.
- **Signs and Symptoms of Exposure:** Shortness of breath, difficulty breathing, coughing and phlegm production and more colds or infections than usual.
- **Medical Conditions Generally Aggravated by Exposure:** Any breathing problems or upper respiratory ailments.
- **Emergency & First Aid Procedures:**
 - Eyes:** Flush with plenty of water for at least 15 minutes—Call a physician.
 - Skin:** Wash thoroughly with soap and water—if irritation persists, call a physician
 - Inhalation:** Remove to fresh air.
 - Ingestion:** May cause an obstruction—Call a physician immediately.

7. PRE-CAUTION FOR SAFE HANDING AND USE

- **Steps to taken in case material is released or spilled:** Sweep up but avoid creating excessive dust. The addition of water will cause the material to set up.
- **Waste Disposal Method:** Follow all federal, state and local regulations at any solid waste disposal facility. A slurry may plug drains.
- **Precautions to be taken in handling and storage:** Use a dustless system for storage and cleanup if possible. Use a vacuum system to control dust. Keep equipment well maintained to help control dust.
- **Other Precautions:** Protect skin from prolonged contact with wet cement. Wet cement can cause burns without warning.

8. CONTROL MEASURES

- **Respiratory Protection (Type):** Respirator as specified in OSHA Standard #1910.134
- **Ventilation:**
 - Local Exhaust:** Try not to get dust airborne.
 - Mechanical (General):** N/A
 - Special:** Provide constant flow of fresh air during application.
 - Other:** N/A
- **Protective Gloves:** Barrier Cream Neoprene, or Rubber Gloves
- **Eye Protection:** Safety Goggles if preferred. Have eye bath in vicinity of use.
- **Work Hygienic Practices:** Practice good housekeeping. Any food or drink should be protected from the dust. Use good personal hygiene practices.

9. OTHER INFORMATION

This information is based our present knowledge. However, this shall not constitute a guarantee for any specific product feature and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS: Environmental, Health and Safety department**
- **Contact: Daniel L. Huckabee**