

Non-Skid™

Non-Skid Wax Additive



PRODUCT INFORMATION

PACKAGING

NON-SKID™ 2 1/2 lb can

Screen Analysis: Maximum Particle Size (microns)
50 Mesh-300

Microtrac Laser Analysis: Mean Particle Size
(microns) 50:160-180

DESCRIPTION

NON-SKID™ waxes are micronized polypropylenes that are manufactured using special equipment to provide a unique texturizing agent. The particle size is carefully controlled to produce a uniform textured surface in paints and coatings. NON-SKID™ will also impart a smoother "feel" than other types of texturizing agents due to its rounded, almost spherical shape. The particle size is controlled using screens.

LIMITED WARRANTY NOTICE

Contract Packaging Inc. products are designed to be used in the construction industry and should be applied by competent persons in accordance with current published instructions. We cannot be held responsible for difficulty caused by other materials and conditions, or by inferior workmanship. Seller reserves the right to have the true cause of any difficulty determined by accepted test methods by an independent party. Any claim regarding product defect must be received in writing (1) year from day of shipment. No claim will be considered without such written notice or after the specified time interval.

ADVANTAGES

The physical properties of polypropylene make NON-SKID™ ideally suited as a texturizing agent. The low density and insolubility characteristics of NON-SKID™ will reduce or eliminate settling and provide optimum performance in aromatic systems. The high melting point of NON-SKID™ will insure a consistent texture even a high baking temperatures. The rounded shape of NON-SKID™ will provide optimum abrasion resistance, gloss control and will be less abrasive when compared to silica texturizing agents.

DISCLAIMER OF WARRANTIES AND LIMITATIONS OF LIABILITY

Contract Packaging Inc. (Seller) warrants that if any goods supplied prove defective in workmanship or material that Seller shall replace them or refund their purchase price. This warranty is made in lieu of any and all other warranties, expressed or implied. Including the warranties of merchantability and/or fitness, which are hereby disclaimed. It is understood and agreed that buyer's sole remedy, and therefore Seller's liability, whether in contract, tort, under any warranty, in negligence, or otherwise shall be limited to the return of the purchase price paid by purchaser or replacement of any defective goods sold by Seller and under no circumstances shall Seller be liable for special, indirect or consequential damages. The price stated for the goods is a consideration in limiting Seller's liability. Any liability or risk resulting from the use of this product is assumed by the purchaser/user except where a specific warranty is provided by the manufacturer in writing. Before application, the purchaser/user shall determine the suitability of the product for his intended use and purchaser/user assumes all liabilities and risk, whatsoever in connection therewith. The terms of this warranty notice may not be orally modified. Any substitutions will void warranty.

USE

NON-SKID™ is recommended for use in industrial paints, lacquers and coatings (e.g. wood, metal, powder or spray). The level of addition depends on the degree of texture desired.

Add 5-10% by weight, based upon resin solids of NON-SKID™ for a moderate textured finish.

Since NON-SKID™ can be dispersed into all types of paint and coatings using a high speed mixer, the need for pre-dispersion is eliminated.

PROPERTIES

Mesh: 50 (Screen Analysis 300)

Melting Point degrees F (ASTM D-127) 50:330-335

Melting Point degrees C (ASTM D-127) 50:166-168

Density @ 25 degrees C g/cc 50:0.90

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com