

Poof!™*Makes Hardened Concrete Disappear*

PRODUCT / APPLICATION GUIDE

IMPORTANT NOTICE!!!

DO NOT WET CONCRETE WITH WATER PRIOR TO APPLYING POOF!™

DESCRIPTION

POOF!™ makes hardened concrete disappear.

APPLICATION

1. Completely saturate area of hardened concrete to be removed with POOF! via sprayer or soft brush. (DO NOT DILUTE) Concrete will turn white upon contact, then darken. IF ALLOWED TO EVAPORATE, WHITE RESIDUE WILL APPEAR. DO NOT RINSE. RE-APPLY Poof!™ TO REACTIVATE AS NEEDED UNTIL CONCRETE IS SOFTENED.
2. Allow POOF!™ to penetrate 10-15 minutes. After 10-15 minutes, re-apply POOF!™ to same area. Keep surface wet with POOF!™. Concrete will begin to soften and pull away from cleaned surface. (Approximately 20-30 minutes)
3. Rinse with water pressure thoroughly. ON EXTRA THICK BUILDUP, REPEAT CLEANING DIRECTIONS UNTIL BUILDUP IS SOFT.

SURFACE / AIR TEMPERATURES

Do not clean with any type product when temperatures are below freezing or extreme heat of direct sun. Best cleaning results are obtained when air and surface temperatures are 40 degrees F to 80 degrees F. (Hot surface temperature may cause scorching.)

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type surface being cleaned. Test also to determine the desired surface contact time and potential for adverse reactions with application. Allow test panels to dry thoroughly before evaluating final appearance and results.

NOTES

ALWAYS WEAR EYE PROTECTION WHEN HANDLING ANY TYPE OF CHEMICAL. AS WITH ANY CHEMICAL, POOF!™ SHOULD NOT BE APPLIED TO EXTREMELY HOT SURFACES. SCORCHING MAY OCCUR!

LIMITED WARRANTY NOTICE

Contract Packaging Inc. products are designed to be used in the construction industry and should be applied by competent persons in accordance with current published instructions. We cannot be held responsible for difficulty caused by other materials and conditions, or by inferior workmanship. Seller reserves the right to have the true cause of any difficulty determined by accepted test methods by an independent party. Any claim regarding product defect must be received in writing (1) year from day of shipment. No claim will be considered without such written notice or after the specified time interval.

DISCLAIMER OF WARRANTIES AND LIMITATIONS OF LIABILITY

Contract Packaging Inc. (Seller) warrants that if any goods supplied prove defective in workmanship or material that Seller shall replace them or refund their purchase price. This warranty is made in lieu of any and all other warranties, expressed or implied. Including the warranties of merchantability and/or fitness, which are hereby disclaimed. It is understood and agreed that buyer's sole remedy, and therefore Seller's liability, whether in contract, tort, under any warranty, in negligence, or otherwise shall be limited to the return of the purchase price paid by purchaser or replacement of any defective goods sold by Seller and under no circumstances shall Seller be liable for special, indirect or consequential damages. The price stated for the goods is a consideration in limiting Seller's liability. Any liability or risk resulting from the use of this product is assumed by the purchaser/user except where a specific warranty is provided by the manufacturer in writing. Before application, the purchaser/user shall determine the suitability of the product for his intended use and purchaser/user assumes all liabilities and risk, whatsoever in connection therewith. The terms of this warranty notice may not be orally modified. Any substitutions will void warranty.

Manufactured by

CONTRACT PACKAGING INC.

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - www.koverkrete.com