

# Super Stripper™

Professional Paint Stripper



K  
O  
V  
E  
R  
  
K  
R  
E  
T  
E  
™  
  
S  
Y  
S  
T  
E  
M  
S

## PRODUCT AND APPLICATION GUIDE

### PACKAGING

Super Stripper™ ..... 5 gal. pails

### Coverage

Horizontal - 200 sq. ft. per gal.

Vertical - 130 sq. ft. per gal.

### USES

- Lead-based paint removal
- Latex paint removal
- Enamel paint removal
- Two part epoxies (solid count must be lower than 40%)
- Urethane removal
- Varnish removal
- Strip a wood floor without the odor and dust

### DESCRIPTION

Super Stripper™ is an industrial strength and consumer friendly paint, varnish, and urethane remover made from 100% American grown soybeans. The low evaporation rate of Super Stripper™ and its gel formulation make it possible to remove several layers of paint in one application. During the removal of lead based paint, lead becomes encapsulated in the gel, preventing air born lead particles, allowing for safe and easy disposal. Super Stripper™ contains no methylene chloride, is not an alkaline based stripper and cleans up easily with water. Unlike more traditional paint strippers Super Stripper™ lets us work without the odor. Indoors or outdoors, you can be guaranteed a safe restoration process with Super Stripper™.

### APPLICATION

Super Stripper™ is safe to use on wood, brick stone, concrete, metal, plaster, and many other surfaces. Do not use on plastic, PVC, rubber or dry wall. Super Stripper™ may be used indoors or outdoors. If used outdoors, tenting with a thin mil, plastic drop cloth will prevent the wind from prematurely drying the area. Super Stripper™ may be used on vertical, as well as horizontal projects.

Use a brush or airless sprayer to apply a uniform coating of Super Stripper™ 1/8" inch thick. If using a brush, do not apply as in painting by over brushing previous strokes. Use the brush to lay the Super Stripper™ on the surface. The number of layers and type(s) of coating(s) will determine the amount of time needed for Super Stripper™ to work. Check the progress of the stripping action by using a scrapper to see if the coating has been lifted from the surface. If not, wait longer and re-check. As long as Super Stripper™ is wet, it is working. Let the stripper do the work. Once the coating is lifted from the surface, remove it with a scrapper or other stripping tool. Clean the remaining thin residue with water and a fibrous scrub pad.

### PRECAUTIONS

If used on fiber glass surface and dulling occurs, restore luster by using rubbing compound. For prolonged periods, 18 hours or more, damage could occur. For veneer finishes, exposure should be in short intervals, 5-10 minutes. Longer exposure times could result in damage. Not for use on PVC.

### PROPERTIES

- Flash Point: Above 200°F
- pH Level: 6.80 pH of 1/10 wt/wt solution soft water.
- Vapor Pressure: Not determined
- Odor: Mild Odor
- Conditions to avoid: Strong Oxidizing agents.
- Health Hazards: May cause moderate eye irritation. May cause delayed skin irritation. May be harmful if swallowed in large amounts.

Manufactured by

**CONTRACT PACKAGING INC.**

22 N. Dollins Avenue - Orlando, FL 32805

Tel. (407) 246-7797 - Fax. (407) 481-2261 - [www.koverkrete.com](http://www.koverkrete.com)

## **LIMITED WARRANTY NOTICE**

Contract Packaging Inc. products are designed to be used in the construction industry and should be applied by competent persons in accordance with current published instructions. We cannot be held responsible for difficulty caused by other materials and conditions, or by inferior workmanship. Seller reserves the right to have the true cause of any difficulty determined by accepted test methods by an independent party. Any claim regarding product defect must be received in writing (1) year from day of shipment. No claim will be considered without such written notice or after the specified time interval.

## **DISCLAIMER OF WARRANTIES AND LIMITATIONS OF LIABILITY**

Contract Packaging Inc. (Seller) warrants that if any goods supplied prove defective in workmanship or material that Seller shall replace them or refund their purchase price. This warranty is made in lieu of any and all other warranties, expressed or implied. Including the warranties of merchantability and/or fitness, which are hereby disclaimed. It is understood and agreed that buyer's sole remedy, and therefore Seller's liability, whether in contract, tort, under any warranty, in negligence, or otherwise shall be limited to the return of the purchase price paid by purchaser or replacement of any defective goods sold by Seller and under no circumstances shall Seller be liable for special, indirect or consequential damages. The price stated for the goods is a consideration in limiting Seller's liability. Any liability or risk resulting from the use of this product is assumed by the purchaser/user except where a specific warranty is provided by the manufacturer in writing. Before application, the purchaser/user shall determine the suitability of the product for his intended use and purchaser/user assumes all liabilities and risk, whatsoever in connection therewith. The terms of this warranty notice may not be orally modified. Any substitutions will void warranty.